

9PX UPS: RACKMOUNT SPECIFICATIONS

208-240 VAC 4500 - 9990 WATTS

SYSTEM CONFIGURATION		MODEL NUMBER	RUNTIME (full / half load)	UPS MODULE ** (H" x W" x D") (lbs.)		BATTERY SYSTEM (H" x W" x D") (lbs.)		INPUT BREAKER ***
4500 Watts		DS9PXXR4500N003S	3m / 11m	10.2 x 17.3 x 28.4	203	Internal	---	30A @ 240V
Wiring Type:	Softwired	DS9PXXR45001020S	20m / 48m	10.2 x 17.3 x 28.4	203	5.1 x 17.3 x 25.4	150	30A @ 240V
Input Volts:	208V or 240V							
Input Type:	L6-30P	DS9PXXR45002038S	38m / 88m	10.2 x 17.3 x 28.4	203	10.2 x 17.3 x 25.4	300	30A @ 240V
Output Volts:	208-240/120V							
Output Type:	L14-30R, L6-30R & (6) 5-20R	DS9PXXR45003054S	54m / 124m	10.2 x 17.3 x 28.4	203	15.3 x 17.3 x 25.4	450	30A @ 240V
Isolation:	Yes	DS9PXXR45004080S	80m / 168m	10.2 x 17.3 x 28.4	203	20.4 x 17.3 x 25.4	600	30A @ 240V
Maint. Bypass:	Yes							
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.								
4500 Watts		DS9PXXR4500N003H	3m / 11m	10.2 x 17.3 x 28.4	201	Internal	---	30A @ 240V
Wiring Type:	Hardwired	DS9PXXR45001020H	20m / 48m	10.2 x 17.3 x 28.4	201	5.1 x 17.3 x 25.4	150	30A @ 240V
Input Volts:	208V or 240V							
Input Type:	Hardwired	DS9PXXR45002038H	38m / 88m	10.2 x 17.3 x 28.4	201	10.2 x 17.3 x 25.4	300	30A @ 240V
Output Volts:	208-240/120V							
Output Type:	Hardwired	DS9PXXR45003054H	54m / 124m	10.2 x 17.3 x 28.4	201	15.3 x 17.3 x 25.4	450	30A @ 240V
Isolation:	Yes	DS9PXXR45004080H	80m / 168m	10.2 x 17.3 x 28.4	201	20.4 x 17.3 x 25.4	600	30A @ 240V
Maint. Bypass:	Yes							
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.								
5400 Watts*		DS9PXXR5400N003S	3m / 8m	10.2 x 17.3 x 28.4	203	Internal	---	30A @ 240V
Wiring Type:	Softwired	DS9PXXR54001016S	16m / 38m	10.2 x 17.3 x 28.4	203	5.1 x 17.3 x 25.4	150	30A @ 240V
Input Volts:	208V or 240V							
Input Type:	L6-30P	DS9PXXR54002028S	28m / 71m	10.2 x 17.3 x 28.4	203	10.2 x 17.3 x 25.4	300	30A @ 240V
Output Volts:	208-240/120V							
Output Type:	L14-30R, L6-30R & (6) 5-20R	DS9PXXR54003047S	47m / 104m	10.2 x 17.3 x 28.4	203	15.3 x 17.3 x 25.4	450	30A @ 240V
Isolation:	Yes	DS9PXXR54004058S	58m / 133m	10.2 x 17.3 x 28.4	203	20.4 x 17.3 x 25.4	600	30A @ 240V
Maint. Bypass:	Yes							
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.								
5400 Watts*		DS9PXXR5400N003H	3m / 8m	10.2 x 17.3 x 28.4	201	Internal	---	30A @ 240V
Wiring Type:	Hardwired	DS9PXXR54001016H	16m / 38m	10.2 x 17.3 x 28.4	201	5.1 x 17.3 x 25.4	150	30A @ 240V
Input Volts:	208V or 240V							
Input Type:	Hardwired	DS9PXXR54002028H	28m / 71m	10.2 x 17.3 x 28.4	201	10.2 x 17.3 x 25.4	300	30A @ 240V
Output Volts:	208-240/120V							
Output Type:	Hardwired	DS9PXXR54003047H	47m / 104m	10.2 x 17.3 x 28.4	201	15.3 x 17.3 x 25.4	450	30A @ 240V
Isolation:	Yes	DS9PXXR54004058H	58m / 133m	10.2 x 17.3 x 28.4	201	20.4 x 17.3 x 25.4	600	30A @ 240V
Maint. Bypass:	Yes							
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.								
7200 Watts		DS9PXXD7200N005H	5m / 16m	10.2 x 17.3 x 30.0	205	Internal	---	50A @ 240V
Wiring Type:	Hardwired	DS9PXXD72001016H	16m / 36m	10.2 x 17.3 x 30.0	205	5.1 x 17.3 x 25.4	150	50A @ 240V
Input Volts:	208V or 240V							
Input Type:	Hardwired	DS9PXXD72002027H	27m / 65m	10.2 x 17.3 x 30.0	205	10.2 x 17.3 x 25.4	300	50A @ 240V
Output Volts:	Same as input							
Output Type:	Hardwired or (3) L6-30R	DS9PXXD72003036H	36m / 80m	10.2 x 17.3 x 30.0	205	15.3 x 17.3 x 25.4	450	50A @ 240V
Isolation:	No	DS9PXXD72004050H	50m / 118m	10.2 x 17.3 x 30.0	205	20.4 x 17.3 x 25.4	600	50A @ 240V
Maint. Bypass:	Yes							
4-post rack or cabinet installation only		DS9PXXD72005065H	65m / 143m	10.2 x 17.3 x 30.0	205	25.5 x 17.3 x 25.4	750	50A @ 240V
Contact SEPS for information about longer runtimes and output power distribution options.								
9990 Watts*		DS9PXXD9990N003H	3m / 10m	10.2 x 17.3 x 30.0	205	Internal	---	70A @ 240V
Wiring Type:	Hardwired	DS9PXXD99901010H	10m / 25m	10.2 x 17.3 x 30.0	205	5.1 x 17.3 x 25.4	150	70A @ 240V
Input Volts:	208V or 240V							
Input Type:	Hardwired	DS9PXXD99902018H	18m / 42m	10.2 x 17.3 x 30.0	205	10.2 x 17.3 x 25.4	300	70A @ 240V

Output Volts:	Same as input								
Output Type:	Hardwired or (3) L6-30R	DS9PXXD99903025H	25m / 61m	10.2 x 17.3 x 30.0	205	15.3 x 17.3 x 25.4	450	70A @ 240V	
Isolation:	No	DS9PXXD99904034H	34m / 79m	10.2 x 17.3 x 30.0	205	20.4 x 17.3 x 25.4	600	70A @ 240V	
Maint. Bypass:	Yes	DS9PXXD99905042H	42m / 98m	10.2 x 17.3 x 30.0	205	25.5 x 17.3 x 25.4	750	70A @ 240V	
4-post rack or cabinet installation only									

Contact SEPS for information about longer runtimes and output power distribution options.

9PX UPS: RACKMOUNT ACCESSORIES

MODEL NUMBER	DESCRIPTION	DIMENSIONS *	
		(H" x W" x D")	(lbs.)
DS9PXXEBM4500R	Extended Battery Module for 9PX 4500W and 5400W models, including mounting hardware.	5.1 x 17.3 x 25.4	150
DS9PXXEBM7200D	Extended Battery Module for 9PX 7200W and 9990W models, including 4-post mounting hardware.	5.1 x 17.3 x 25.4	150
DS9PXXNETCARD	Network/SNMP Card for all 9PX models.	Internal	1
DS9PXXRELAY	Relay Card for all 9PX models.	Internal	1

* 208V output derates the 5400W unit to 4800W and the 9990W unit to 9000W. Runtimes will increase slightly.

** Includes PowerPass Distribution (Bypass) Module. Consult the 9PX User Manual for installation and service clearances.

*** Always consult the 9PX User Manual and local electrical codes to verify the proper input breaker size.



800.369.7377