

9PX UPS: RACKMOUNT SPECIFICATIONS

120 VAC 630 - 2700 WATTS

SYSTEM CONFIGURATION	MODEL NUMBER	RUNTIME (full / half load)	UPS MODULE ** (H" x W" x D") (lbs.)	BATTERY SYSTEM (H" x W" x D") (lbs.)	INPUT BREAKER ***
630 Watts	DS9PXXR0630N011S	11m / 27m	3.4 x 17.3 x 17.7 36	Internal ---	15A @ 120V
Wiring Type: Softwired	DS9PXXR06301037S	37m / 84m	3.4 x 17.3 x 17.7 36	3.4 x 17.3 x 17.7 48	15A @ 120V
Input Volts: 120V					
Input Type: 5-15P	DS9PXXR06302067S	67m / 151m	3.4 x 17.3 x 17.7 36	6.8 x 17.3 x 17.7 96	15A @ 120V
Output Volts: 120V					
Output Type: (8) 5-15R	DS9PXXR06303099S	99m / 226m	3.4 x 17.3 x 17.7 36	10.2 x 17.3 x 17.7 144	15A @ 120V
Isolation: No	DS9PXXR06304134S	134m / 305m	3.4 x 17.3 x 17.7 36	13.6 x 17.3 x 17.7 192	15A @ 120V
Maint. Bypass: Optional					
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.					
900 Watts	DS9PXXR0900N006S	6m / 18m	3.4 x 17.3 x 17.7 36	Internal ---	15A @ 120V
Wiring Type: Softwired	DS9PXXR09001024S	24m / 56m	3.4 x 17.3 x 17.7 36	3.4 x 17.3 x 17.7 48	15A @ 120V
Input Volts: 120V					
Input Type: 5-15P	DS9PXXR09002043S	43m / 100m	3.4 x 17.3 x 17.7 36	6.8 x 17.3 x 17.7 96	15A @ 120V
Output Volts: 120V					
Output Type: (8) 5-15R	DS9PXXR09003064S	64m / 149m	3.4 x 17.3 x 17.7 36	10.2 x 17.3 x 17.7 144	15A @ 120V
Isolation: No	DS9PXXR09004086S	86m / 202m	3.4 x 17.3 x 17.7 36	13.6 x 17.3 x 17.7 192	15A @ 120V
Maint. Bypass: Optional					
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.					
1350 Watts	DS9PXXR1350N005S	5m / 16m	3.4 x 17.3 x 17.7 43	Internal ---	15A @ 120V
Wiring Type: Softwired	DS9PXXR13501026S	26m / 62m	3.4 x 17.3 x 17.7 43	3.4 x 17.3 x 17.7 60	15A @ 120V
Input Volts: 120V					
Input Type: 5-15P	DS9PXXR13502049S	49m / 115m	3.4 x 17.3 x 17.7 43	6.8 x 17.3 x 17.7 120	15A @ 120V
Output Volts: 120V					
Output Type: (8) 5-15R	DS9PXXR13503074S	74m / 173m	3.4 x 17.3 x 17.7 43	10.2 x 17.3 x 17.7 180	15A @ 120V
Isolation: No	DS9PXXR13504100S	100m / 233m	3.4 x 17.3 x 17.7 43	13.6 x 17.3 x 17.7 240	15A @ 120V
Maint. Bypass: Optional					
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.					
1800 Watts	DS9PXXR1800N008S	8m / 20m	3.4 x 17.3 x 23.8 63	Internal ---	20A @ 120V
Wiring Type: Softwired	DS9PXXR18001030S	30m / 76m	3.4 x 17.3 x 23.8 63	3.4 x 17.3 x 23.8 87	20A @ 120V
Input Volts: 120V					
Input Type: 5-20P	DS9PXXR18002060S	60m / 139m	3.4 x 17.3 x 23.8 63	6.8 x 17.3 x 23.8 174	20A @ 120V
Output Volts: 120V					
Output Type: (6) 5-20R & (1) L5-20R	DS9PXXR18003090S	90m / 208m	3.4 x 17.3 x 23.8 63	10.2 x 17.3 x 23.8 261	20A @ 120V
Isolation: No	DS9PXXR18004120S	120m / 281m	3.4 x 17.3 x 23.8 63	13.6 x 17.3 x 23.8 348	20A @ 120V
Maint. Bypass: Optional					
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.					
2700 Watts	DS9PXXR2700N005S	5m / 14m	3.4 x 17.3 x 23.8 63	Internal ---	30A @ 120V
Wiring Type: Softwired	DS9PXXR27001023S	23m / 53m	3.4 x 17.3 x 23.8 63	3.4 x 17.3 x 23.8 87	30A @ 120V
Input Volts: 120V					
Input Type: L5-30P	DS9PXXR27002043S	43m / 97m	3.4 x 17.3 x 23.8 63	6.8 x 17.3 x 23.8 174	30A @ 120V
Output Volts: 120V					
Output Type: (6) 5-20R & (1) L5-30R	DS9PXXR27003064S	64m / 145m	3.4 x 17.3 x 23.8 63	10.2 x 17.3 x 23.8 261	30A @ 120V
Isolation: No	DS9PXXR27004086S	86m / 196m	3.4 x 17.3 x 23.8 63	13.6 x 17.3 x 23.8 348	30A @ 120V
Maint. Bypass: Optional					
NOTE: UPS equipment may be installed in either a 4-post or 2-post rack/cabinet with included hardware.					

9PX UPS: RACKMOUNT ACCESSORIES

MODEL NUMBER	DESCRIPTION	DIMENSIONS (H" x W" x D") (lbs.)
DS9PXXEBM0900R	Extended Battery Module for 9PX 630W and 900W models.	3.4 x 17.3 x 17.7 48
DS9PXXEBM1350R	Extended Battery Module for 9PX 1350W models.	3.4 x 17.3 x 17.7 60
DS9PXXEBM1800R	Extended Battery Module for 9PX 1800W and 2700W models, including mounting hardware.	3.4 x 17.3 x 23.8 87
DS9PXXNETCARD	Network/SNMP Card for all 9PX models.	Internal 1
DS9PXXRELAY	Relay Card for all 9PX models.	Internal 1
DS9PXXMBP1	HotSwap Maintenance Bypass for 630W to 1350W 9PX UPS - (6) 5-15R Output.	2.1 x 17.3 x 3.8 5
DS9PXXMBP2	HotSwap Maintenance Bypass for 1800W 9PX UPS - (6) 5-20R Output.	2.1 x 17.3 x 3.8 5
DS9PXXMBP3	HotSwap Maintenance Bypass for 2700W 9PX UPS - (5) 5-20R Output.	2.1 x 17.3 x 3.8 5

*** Always consult the 9PX User Manual and local electrical codes to verify the proper input breaker size.

